

Suzuki Instruments

Suzuki Genuine Instruments are custom-designed to provide the quality, reliability and value you expect from Suzuki Products. The wide selection allows you to accurately monitor a variety of essential functions. All instruments are lighted for night time boating and feature standard 2" and 4" diameters for easy installation.



37860-87L00
Trolling Switch

34200-93J20
4" Tachometer

34200-93J00
4" Tachometer / Monitor



34800-93J00
2" Trim Meter



34500-93J00
2" Hour Meter

34200-93J40
4" Tachometer / Trolly Mode



34100-93J00
4" Speedometer



34300-93J00
2" Fuel Gauge



34600-93J00
2" Voltmeter



34650-93J20
2" Water Pressure Gauge 15 psi

4" Tachometer With Suzuki Troll Mode Scale

Easy to read 4" Tachometer has a scale from 0-7,000 RPMs for standard use, and a secondary scale from 0-3,000 RPMs with markers at 50 RPM intervals for use with the Suzuki Troll Mode System*. Gauge also includes warning lamps for Engine Temperature, Low Oil, Check Engine and Over-Rev. When in troll mode, Over-Rev lamp stays on to indicate that Troll mode has been engaged. The secondary RPM scale is designed to make setting and maintaining a lower troll speed simple. Fits DF40A/50A/50AV/60A/60AV/70A/90A/115A/140A/150G/175G/200A/250AP/300AP (DF300/200AP requires SMIS gauges).

*See engine owner's manual for information about Suzuki Troll Mode system. Not all models come equipped with trolling mode system. Accessory Troll Mode Switch required for Suzuki Troll Mode System use. Suzuki recommends the use of this gauge for trolling use.

34200-93J40 DF40A/50A/50AV/60A/60AV/70A/90A/115A/140A/150G/175G/200A/250AP/300AP (DF300/200AP with SMIS gauges)

Trolling Mode Control Switch

Allows the use of the Suzuki Troll Mode on equipped engines. When Troll mode is engaged, this switch allows for adjustments of engine RPM in 50 RPM increments, from idle to 1200 RPM to make setting and maintaining a trolling speed easy. Consult owner's manual or Suzuki Outboard Dealer for additional details on Suzuki Troll System operation.

37860-87L00 trolling switch

4" Tachometers

7,000 max R.P.M. Tachs are available with or without 4-Stroke monitor functions. Monitor functions include: Low Oil Pressure Warning, Engine Temperature Warning, Check Engine Warning and Over-Rev Limit Warning.

34200-93J00 with monitor functions 34200-93J20 without monitor

2" Trim Meter

Magnetic type gauge shows trim angle for optimum performance and efficiency.

34800-93J00 Black

2" Hour Meter

12 volt electric motor driven meter indicates the number of hours your outboard motor has been operated to indicate when periodic services are necessary.

34500-93J00 Black

4" Speedometers

Bourdon-tube type speedometer with readings in M.P.H. and Km/h. Includes vinyl tube, plus all installation instructions and hardware. *Pitot tube 34190-87D00 must be ordered separately for DF50 and under models.

34100-93J00 80 mph 34100-93J20 50 mph (not shown)
34190-87D00* Pitot Tube (not shown)

2" Fuel Gauge

Operates on 12 volts with magnetically damped needle. Works with most fuel tank sending units.

34300-93J00 Black

2" Voltmeter

A well charged battery is essential for quick and easy starts. Monitor the charging system using a Voltmeter.

34600-93J00 Black

2" Water Pressure Gauge 15 psi

Bourdon-tube type gauge measures cooling water pressure. Instructions and dash installation hardware included. Order Installation kit for appropriate model.

34650-93J20 Black

Water Pressure Gauge Installation Kits

Kit includes fittings and hoses needed for motor to gauge connection.

34660-93J00 DF200/225/250/250AP/300AP 34660-96J00 DF150/175/200A
34660-99E00 DF60/70 34660-87J00 DF40/50
34660-90J02 DF40A/50A/50AV/60A/60AV/70A/80A/90A/115/115A/140/140A